

WIRELESS GLASS BREAK DETECTOR

2GIG-GB1-345



The Glass Break Detector (2GIG-GB1-345) is a fully-supervised, tamper-protected, ceiling- or wall-mounted unit. It communicates with the 2GIG Control Panel using the 345 MHz frequency. The detector provides a 15 ft (4.6 m) maximum detection range, 360° maximum horizontal sensing angle, and dual-stage glass break detection.

SPECIFICATIONS

Wireless Signal Range	300 ft (91.44 m), open air, with Wireless Control Panel
Code Outputs	Alarm; Alarm Restore; Tamper; Tamper Restore; Supervisory; Low Battery
Transmitter Frequency	345.000 MHz (crystal controlled)
Unique ID Codes	Over one (1) million different code combinations
Supervisory Interval	70 minutes
Sensor Type	Single microphone, dual stage thud, and crash
Maximum Horizontal Sensing Angle	360° for ceiling mount or 180° for wall mount
Dimensions (D x H)	4.55 x 1.9 in (11.56 x 4.83 cm)
Weight (including battery & bracket)	5.1 oz (144.6 g)
Housing Material	ABS Plastic
Color	White
Operating Temperature	32°-120° F (0°-49° C)
Relative Humidity	5-90% Non-Condensing
Battery (installed)	Two (2) CR 123A 3V or equivalent Lithium batteries
Approved Glass Break Simulator	FG-701 Glassbreak Simulator
Certification	Anatel, ETL, FCC, IC, IFETEL, and NOM