

WIRELESS KEYPAD

2GIG-PAD1-345



The Wireless Keypad (2GIG-PAD1-345) is a wall-mounted unit designed for use as a secondary keypad for the 2GIG alarm system. It communicates with the Go!Control Panel using the 345 MHz frequency. It also provides users with the ability to arm the system in Stay or Away mode, disarm the system, as well as to activate Fire and Panic emergency functions.

SPECIFICATIONS

Wireless Signal Range	350 ft (106.7 m), open air, with Wireless Control Panel
Code Outputs	Key Press 0-9; *, #; Stay; Away; Fire; Police; Supervisory; Low Battery
Transmitter Frequency	345.000 MHz (crystal controlled)
Unique ID Codes	Over one (1) million different code combinations
Supervisory Interval	70 minutes
Peak Field Strength	Typical 50,000 uV/m at 3m
Dimensions (L x W x H)	5.73 x 4.25 x 1.00 in (14.6 x 0.8 x 2.5 cm)
Weight (including battery)	7.75 oz (219.7 g)
Housing Material	ABS Plastic
Color	White with Silver Trim
Operating Temperature	32°-120 F° (0°-49° C)
Relative Humidity	5-90% Non-Condensing
Battery (installed)	Two (2) CR 2032 3V or equivalent Lithium coin batteries
Certification	Anatel, ETL, FCC, IC, IFETEL, and NOM

Nortek Security & Control | 1950 Camino Vida Roble Suite 150 | Carlsbad, CA 92008 | USA | 800.421.1587 | nortekcontrol.com | dealer.2gig.com

Copyright © 2015 Nortek Security & Control. All Rights Reserved. Linear and Go!Control are registered trademarks of Linear LLC. All other products or name brands are either trademarks or registered trademarks of their respective holders. Specifications and product availability subject to change without notice. For more information, contact your local Nortek Security & Control or 2GIG dealer for pricing or visit nortekcontrol.com or dealer.2gig.com.