


# AVR-NSV16E2N

16 CH. 4K UHD NETWORK  
VIDEO RECORDER



## H.265 4K UHD NETWORK VIDEO RECORDER

8MP / 5MP / 3MP / 2MP / 1080P / 960P / 720P  
**DUAL ETHERNET / DUAL HDMI**



### FUNCTION

- H.265 codec decoding
- 160Mbps(16CH) input bandwidth
- Up to 8MP(4K) resolution for preview and playback
- Support to install up to 2 HDDs, max total capacity of up to 36TB
- Full function network remote view via Internet (CMS, IE/Firefox/Chrome, Mac Safari)
- No limitation on adding devices to CMS, max. 128 channels preview (CMSONE)
- Support scan P2P QR code to connect DVR via Mobile app (AVY Mobile One)
- Support to save pictures/video to Dropbox storage (Dropbox)
- Support to save pictures/video to FTP server (built by user)
- VGA/HDMI output up to 4K resolution
- Support HDD S.M.A.R.T. Monitoring




**AVYCON**<sup>®</sup>

Copyright © AVYCON. All rights reserved. Specifications and pricing are subject to change without notice.

# AVR-NSV16E2N

## 16 CH. 4K UHD NETWORK VIDEO RECORDER




## SPECIFICATIONS

### DESCRIPTION AVR-NSV16E2N

IP Video Input	16 Channels
Output	HDMI x 2: 3840 x 2160(4K) / 2560 x 1440(2K) / 1900 x 1200 / 1600 x 1200 / 1680 x 1050 / 1920 x 1080 / 1440 x 900 / 1280 x 1024 / 1280 x 720 / 1024 x 768 VGA x 1: 1920 x 1080 / 1440 x 900 / 1280 x 1024 / 1280 x 720 / 1024 x 768
Incoming Bandwidth (Mbps)	160Mbps
Outgoing Bandwidth (Mbps)	160Mbps
Video Compression	H.265+/H.265/H.264+/H.264
Audio Compression	G.711a
Installation Wizard	Yes
Resolution	8MP / 5MP / 3MP / 2MP / 1080P / 960P / 720P:30fps
Playback Frame Rate	8MP:45fps, 3MP:90fps, 2MP:180fps
Supported Smart AI	Face Detection, People / Vehicle Detection, License Plate Recognition, Intrusion, Line Crossing, Object Abandonment, People Counting, Crowd Density Detection, Queue Length Detection, Rare Sound Detection, Object Classification and Fisheye Dewarping
Supported Cameras for AI	Diversity Series Network Cameras
Event Triggers	MD(Sensitivity Level 1~8), Video Loss, Beep, Email, Push Notification to Mobile App
Playback Function	Fast forward / backward (2x, 4x, 8x, 16x), Slow forward (1/2x, 1/4x, 1/8x, 1/16x)
Playback	Max 16CH Playback
Local UI	UI5.0
Web Monitoring	IE10/11, Safari V12.1 above, Firefox V.52 above, Chrome V.57 above, Edge V.79 Above
Mobile Viewer	AVY Mobile One
Push Notification	Motion Event, AI, and Abnormal
Reset Button	Password Reset (Hold 3 seconds), Factory Reset (Hold 8 seconds)
HDD Interface	SATA x 2, Max 36TB HDD
PoE	No
Ethernet	2 RJ45 10/100/1000 Base-T
USB	USB 2.0 x 2 (Front & Rear Panel), USB 3.0 x 1 (Rear Panel)
Audio	1 IN / 1 OUT
E-Sata	Yes
RS485	1
Line-In	Yes
Alarm Input/Out	16 IN / 1 OUT
OSD Language	English and More
Power Consumption	6W (Without HDD)
Power Supply	DC12V/2A
Working Environment	32°~104°F (0°~40° Celcius)
Working Humidity	Less than 90%RH (Non-Condensing)
Dimensions	11.81" x 8.93" x 1.97" (300mm x 227mm x 50mm)

## DIMENSIONS

Unit: inch (mm)



## REAR PANEL



## AVAILABLE HDD OPTIONS

- 1TB HDD: AVR-NSV16E2N-1T
- 2TB HDD: AVR-NSV16E2N-2T
- 3TB HDD: AVR-NSV16E2N-3T
- 4TB HDD: AVR-NSV16E2N-4T
- 6TB HDD: AVR-NSV16E2N-6T
- 8TB HDD: AVR-NSV16E2N-8T
- 12TB HDD: AVR-NSV16E2N-12T
- 18TB HDD: AVR-NSV16E2N-18T

## MOBILE APP

AVY Mobile One



Copyright © AVYCON. All rights reserved. Specifications and pricing are subject to change without notice.

phone: 949-752-7606 / 888-833-4611 (Canada Toll-Free)

email: info@avycon.com

social: @avycon\_aivo

website: avycon.com