

# 1 1/2" Miniature Surface Mount Switch Set


WWW.GRISK.COM



## 50 / 50F / 55F Series



- ◆ Excellent for residential applications
  - ◆ Surface mount magnetic contact
- ◆ Self stick or breakaway screw down flange
  - ◆ Center or end 12" #22 AWG leads
- ◆ Longer leads, zip cord or jacketed cable upon request
  - ◆ Hermetically sealed
- ◆ Plated contacts resist sticking or freezing
  - ◆ Mounting hardware included
- ◆ Built in E.O.L. Resistors and Diodes upon request
  - ◆ Supervisory loops upon request
- ◆ Switches and magnets available separately
  - ◆ Colors: white, brown, gray and almond
  - ◆ Lifetime Warranty



### Part Numbers

	<u>Closed Loop</u>	<u>Open Loop</u>	<u>SPDT</u>
Standard Gap 1/2"+	50-12	60-12	70-12
	50F-12	60F-12	70F-12
	55F-12	65F-12	75F-12
Wide Gap 3/4"+	50-12WG	60-12WG	70-12WG
	50F-12WG	60F-12WG	70F-12WG
	55F-12WG	65F-12WG	75F-12WG

**WARRANTY:** Lifetime warranty against workmanship, material and factory defects.

GEORGE RISK INDUSTRIES, INC.  
G.R.I. PLAZA  
KIMBALL, NE 69145  
WWW.GRISK.COM



Made in U.S.A.

TOLL-FREE 1-800-445-5218  
TOLL-FREE 1-800-523-1227  
(308) 235-4645  
FAX (308) 235-3561  
E-MAIL: sales@grisk.com


# 1 1/2" Miniature Surface Mount Switch Set

WWW.GRISK.COM



## INSTALLATION APPLICATIONS

The GRI 50, 50F and 55F series switch sets are the most chosen configurations for residential installations. Low profile and self adhesive 3M tape make installing the sets quick and simple. The 50F and 55F come with a breakaway flange for applications where screws mounts are advisable. The 50 type is self adhesive only. The 50 and 50F have 12" leads exiting the case on the end. The 55F has a 12" lead exiting from the middle of the case. Available in open loop, closed loop and SPDT, regular and wide gap, white, brown, gray and almond. All mounting hardware included.



### GRI PRODUCTS MEET OR EXCEED THESE MINIMUM GENERAL SPECIFICATIONS:

Part Number	Loop Type	Electrical Configuration	Reed Form	Max. Initial Contact Resistance ( $\Omega$ )	Max. Contact Rating (W)	Max. Switching Voltage (VDC)	Max. Switching Current (A)
50-12	Closed	N/O	A	.150	10	200	.500
50F-12	Closed	N/O	A	.150	10	160	.400
55F-12	Closed	N/O	A	.150	10	200	.500
50-12WG	Closed	N/O	A	.150	10	160	.400
50F-12WG	Closed	N/O	A	.150	10	200	.500
55F-12WG	Closed	N/O	A	.150	10	200	.500
60-12	Open	N/C	B	.140	5	175	.250
60F-12	Open	N/C	B	.140	5	175	.250
65F-12	Open	N/C	B	.140	5	175	.250
60-12WG	Open	N/C	B	.140	5	175	.250
60F-12WG	Open	N/C	B	.140	5	175	.250
65F-12WG	Open	N/C	B	.140	5	175	.250
70-12	Open/Closed	SPDT	C	.140	5	175	.250
70F-12	Open/Closed	SPDT	C	.140	5	175	.250
75F-12	Open/Closed	SPDT	C	.140	5	175	.250
70-12WG	Open/Closed	SPDT	C	.140	5	175	.250
70F-12WG	Open/Closed	SPDT	C	.140	5	175	.250
75F-12WG	Open/Closed	SPDT	C	.140	5	175	.250

**WARRANTY:** Lifetime warranty against workmanship, material and factory defects.

GEORGE RISK INDUSTRIES, INC.  
G.R.I. PLAZA  
KIMBALL, NE 69145  
WWW.GRISK.COM



TOLL-FREE 1-800-445-5218  
TOLL-FREE 1-800-523-1227  
(308) 235-4645  
FAX (308) 235-3561  
E-MAIL: sales@grisk.com