

4" 3-Way Indoor/Outdoor Wall-Mount Speaker with Transformer

DMS3TS Black housing
DMS3TSW White housing

Features

- Compact, full-range design
- Each speaker contains:
 - 4" Polypropylene woofer,
 - 2" Polypropylene midrange and
 - 1" Polypropylene dome tweeter
- Die-cast enclosure, complete with mounting bracket, speaker wire and mounting hardware
- Weather-resistant design
- 5 year warranty



Specifications

| | |
|------------------------------|---|
| RMS Power | 15W |
| Max Power..... | 25W |
| Transformer Type | 70/25V (selectable) |
| Transformer Power Taps | 15W, 7.5W, 4W, 2W, 1W & 8 Ohms |
| Termination Type | Screw terminal |
| Sensitivity (1W/1M)..... | 86dB |
| Maximum SPL (Pmax/1m)..... | 97dB |
| Driver Impedance | 8 Ohms |
| Magnet..... | 10 oz. ferrite |
| Frequency Response Range... | 110Hz ~ 20kHz |
| Dispersion @ 1000Hz | 180° conical |
| Driver | 4" polypropylene woofer, 2" mylar midrange, 1" mylar tweeter |
| Speaker Dimensions | 4.5 (W) x 7.25" (H) x 4.375" (D) |
| Weight | 4.2 lbs. |
| Material..... | Body: Aluminum Gille: Treated metal |

NDAA
COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines