



ELEV-P5MIBP37

5 Megapixel IP Plug & Play, Indoor Metal Case Camera, Fixed Lens, D-WDR, Audio Input, PoE/DC12V

Features

- 5 Megapixel (2560 x 1440) Resolution
- Fixed Lens
- H.265/H.265+/H.264/H.264+ Compression
- 20 FPS @ 5 Megapixel
- D-WDR
- Audio Input
- Indoor Only
- 12VDC/PoE Operation
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer
- NDAA Compliant

Camera	
Model	ELEV-P5MIBP37
Sensor+DSP	SC5332 + SSC327DE
Sensor	1/2.7" Progressive scan CMOS Sensor
Min. Illumination	0.01lux (Color), 0lux (IR on)
Lens	3.7mm@F2.0 horizontal FOV:62° , vertical FOV:53°diagonal FOV: 76°
Shutter Time	Auto/Manual, 1/3~1/10000s
Wide Dynamic Range	DWDR
Digital noise reduction	2D/3D DNR
Compression Standard	
Video Compression	H.264/H.264+/H.265/H.265+
H.264 Codec profile	Base/Main/High profile
H.265 Codec profile	Main profile
Video Bit Rate	11 Kbps~8 Mbps
Audio Compression	G.711A/G.711U
Audio Bit Rate	64 Kbps
Image	
Max. Image Resolution	5MP(2592×1944)
Frame Rate	50Hz: 20fps 5MP (2592×1944) 25fps 4MP (2560×1440), 25fps 4MP (2304×1728) 25fps 3MP (2048×1536), 25fps 1080P (1920×1080) 25fps 960P (1280×960), 25fps 720P (1920×720P) 60Hz:15fps 5MP (2592×1944) 25fps 4MP (2560×1440), 25fps 4MP (2304×1728) 30fps 3MP (2048×1536), 30fps 1080P (1920×1080) 30fps 960P (1280×960), 30fps 720P (1280×720)
Sub Stream	20fps D1 (704×576), 20fps CIF (352×288)
Third Stream	20fps CIF (352×288)
Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
BLC	Support
HLC	Support
ROI	Support
Defog	Support
Network	
Protocols	TCP/IP,ICMP,HTTP,HTTPS,DHCP,DNS,DDNS,RTP,RTSP, RTCP,NTP,IGMP,UPnP,SMTP,UPnP-TM,P2P,Bonjour,IPv6
Event	Smart Motion Detection/SMD (Human and Vehicle Classification) Video Shelte
System compatibility	Onvif (Profile S), CGI
Security	User authentication,IP address filtering,Video mask
Mobile Surveillance	iPhone, iPad,Android , CMS, WEB
Interface	
Communication Interface	1 RJ45 10M / 100M Ethernet Port
Audio I/O	1/0
General	
Operating Conditions	14°F ~ 122°F (-10°C ~ 50°C) Humidity 95% or less (non-condensing)
Power Supply	DC12V ± 10%
POE	PoE (802.3af)(External)
Power Consumption	MAX. 3W
Material	Metal
Dimensions	2 x 1.9 x .9 in (51×49×23mm)
Weight	Approx. .44 lb (200g)

Ordering Information

ELEV-P5MIBP37: 5 Megapixel Metal Case Camera, 3.7mm, Black