



## INV-AV131PRO1X2

131 Feet (40M) 1080P@60Hz HDMI 1X2 splitter over Cat6 with IR, with HDMI loop-out on TX, with EDID. Distribute 1 HDMI source to 2 HD displays over network cable simultaneously. Support one HDMI Loop-out. Compatible with CAT6/6a/7 network cables. The transmission distance is 131 Feet (40M). The Highest resolution is up to 1920×1080@60Hz. Support 20~60Hz IR pass back. Support EDID. Plug and play. Wall-mounted function, easy installation.

Technical	Transmitter	Receiver
Input	HDMI×1 ( Type A, 19 pin, female)	
Output	RJ45×2	
Transmission distance	40 meters via CAT6	
Video support	480i@60Hz, 480p@60Hz, 576i@50Hz, 576p@50Hz, 720p@50/60Hz, 1080i@50/60Hz, 1080p@50/60Hz	
Audio format	PCM DTS AC3	
TMDS signal	0.5~1.5Vp-p(TMDS)	
DDC signal	5Vp-p(TTL)	
IR passback function	Support	
IR frequency Range (KHz)	Support 20~60KHz IR frequency devices	
HDMI loopout	Support	
POT (receiver powered from transmitter)	Support	
HDCP	HDCP1.2	
HDMI Distance	1080p: 25 Foot Maximum Distance	
<b>Mechanical</b>		
Housing	Metal enclosure	
Dimensions (L × W ×H)	6.2 x 2.4 x .85 in (157.8 × 62 × 21.6 mm)	2.8 x 2.6 x .9 in (71.6 × 66.6 × 22.6mm)
Net weight	1.4 lb (620g)	.18 lb (80g)
Fixedness	wall-mounting case with screws	
Power supply	5V/2A 1pcs 5V1A 4pcs	
Power consumption	<10W	
Operation temperature	32°F ~140°F (0°C~60°C)	
Storage temperature	-4°F ~140°F (-20°C ~70°C)	
Relative humidity	20~90%(no condensation)	

### Ordering Information

INV-AV131PRO1X2: HDMI Splitter