



## IPOE-INJECTOR2

Vision 60 Watt PoE Injector

### Features

- Full IEEE 802.3af IEEE 802.3at,IEEE802.3at 4Pairs Compliant
- Up to 60W of Power on 4-pairs
- Auto-detect of POE IEEE 802.3af IEEE 802.3at,IEEE802.3at 4Pairs equipment
- Supports 10/100/1000Base-T applications
- LED indicators power input indication
- Distance up to 100 meters
- Internal AC/DC converter – no need for external power brick
- Easy plug-and-play installation
- Surge protection

No. of channels	1
Pass Through Data Rates	10/100/1000Mbps
Power over Ethernet Output	Pin Assignment and Polarity: 1/2 (-), 3/6 (+),4/5 (+), 7/8 (-), Output Power Voltage: 50Vdc User Port Power: 60W
Input Power Requirements	AC Input Voltage: 100 to 240 Vac AC Input Current: 1A 100-240 Vac AC Frequency: 50 to 60 Hz
Dimensions	5.7 x 2.4 x 1.6 in (145mm x 60mm x 40mm)
Indicators	System Indicator: AC Power User Indicator: Channel Power
Connectors	Shielded RJ-45, EIA 568A and 568B
Environmental Conditions	Operating Ambient Temperature: 32 ~ 113°F (0 to 45°C) Operating Humidity Maximum 80%, Non-condensing Storage Temperature: -4 ~ 158 °F (-20 to 70°C) Storage Humidity: Maximum 80%, Non-condensing
Regulatory Compliance	IEEE 802.3af (15.4W) IEEE 802.3at (30W) IEEE802.3at 4Pairs(60W)

### Ordering Information

**IPOE-INJECTOR2:** 60 Watt PoE Injector