## For Use With MS-Series Proximity Readers



### KC-10X
### Standard Light Proximity Card

- Wallet friendly - thinner than other comparable proximity cards
- Extremely durable
- Industry standard formats
- Unique ID codes
- Lifetime Warranty

### MT-10X
### Multi Technology Proximity Card

- ISO thin, just 0.031" (0.8 mm)
- Can also print bar codes
- Unique ID codes

Keri's **KC-10X Standard Light Proximity Card** provides maximum read range performance in a thin package that is easily carried in a wallet or purse or worn on clothing with a clip or lanyard. These cards are extremely durable and convenient. They are manufactured with a vertical hanging slot punch and they come with a lifetime warranty.

The **MT-10X Multi Technology Proximity Card** allows the user to combine several identification technologies in a single credit card thin credential. One of the most popular features of the Multi Technology Cards is that they can accept a direct print video image, typically a photograph, a bar code, and other graphics from most industry standard dye sublimation printers, to create a custom access credential.

The KC-10X Standard Light Card is recommended over the MT-10X Multi Technology Card whenever possible because of its lower cost and lifetime warranty. The Standard Light Cards can be fitted with PVC label or "skin" which can accept a direct printed image to provide photo ID at a much lower cost and greater durability.

Keri **Proximity Credentials** (including Cards, Tags, and Patches) can be used interchangeably on the same system without worry about ID code duplication or format matching.

### KC-10X Standard Light Proximity Card



### MT-10X Multi Technology Proximity Card



Models: MT10X-2P (no mag stripe), MT10X-2S (with HiCo mag stripe)

### Specifications:

**Read Range*:**
MS-3000 up to 4 inches (10 cm)
MS-4000 up to 1 inch (2.5 cm)
MS-5000 up to 8 inches (20 cm)
MS-7000 up to 15 inches (38 cm)

**Size:**
L = 3.38, W = 2.14, T = 0.059 inches
Approx. 86 x 54 x 1.5 mm

**Weight:**
0.31 oz (8.8 g)

**Material:**
ABS

**Frequency:**
125 KHz excitation / 62.5 KHz return

**Temperature:**
-40° C to +70° C

**Humidity:**
0-100% non-condensing

**Color:**
Off white

**Warranty:**
The Standard Light Proximity Card comes with a limited lifetime warranty against defects in materials and workmanship.

### Specifications:

**Read Range*:**
MS-3000 up to 3 inches (7.6 cm)
MS-4000 up to 1 inch (2.5 cm)
MS-5000 up to 4 inches (10 cm)
MS-7000 up to 12 inches (30 cm)

**Size:**
L = 3.38, W = 2.14, T = 0.031 inches
Approx. 86 x 54 x .08 mm

**Weight:**
0.19 oz (5.5 g)

**Material:**
PVC with a printable, gloss surface

**Frequency:**
125 KHz excitation / 62.5 KHz return

*Note: Specifications subject to change without notice. Trademarks are the property of their respective owners.*
*\* Read range is stated in a clean RF and electrical environment with card presented parallel to the reader surface.*

### *ORDERING INFORMATION:*

| Model Number | Description |
|---|---|
| KC-10X | Clamshell NXT Proximity Card for MS Readers |
| MT-10XP | Thin Photo Imagable NXT Proximity Card for MS Readers |
| MT-10XM | Thin Photo Imagable NXT Proximity Card with magnetic stripe for MS Readers |
| PKT-10X | Proximity Key Tag for MS Readers |



*Presented By:*