



PAR-ALLBIRA650DN

5-2 Megapixel Field Selectable TVI/AHD/CVI/CVBS, Outdoor Long Range Bullet, Motorized AF 6-50mm Lens, 361' IR Range, True WDR, Dual Voltage

Features

- 5-2 Megapixel Field Selectable**, Sony Sensor and Korea EyeNix DSP
- All-in-One Technology (TVI/AHD/CVI/Analog 960h),
- Motorized AF 6-50mm lens
- True Day/Night
- True WDR
- 361' Smart IR Range
- Built-in OSD Board, Built-in Dip Switch, Built-in Optional Video Output
- Up The Cable (UTC) Function
- IP67 Weatherproof
- Dual Voltage
- Through InVid Tech DVR: Free App, CMS & MAC Client
- NDAA Compliant

*Scale down to other resolutions via camera dip switches & OSD

Camera	
Filter	Removable IR Cut Filter
Image Sensor	1/2.8" 5Mega-pixel Sony CMOS
Pixels	Total: 2704(H)*2104(V), Effective: 2616(H)*1964(V)
Video Output	TVI:5MP 20/12.5 FPS, 4MP/2MP 30/25 FPS AHD:5MP 20/12.5 FPS, 4 MP / 2MP 30/25 FPS CVI:4MP 30/25 FPS, 2 MP 30/25 FPS CVBS
Video Output By Default	TVI: 5MP @ 20 FPS AHD:5MP @ 30 FPS CVI: 4MP @ 30 FPS CVBS
Min Illumination	0Lux(12PCs led ON)
Vertical Frequency	NTSC:60Hz PAL:50Hz
IR Range	361 Feet
S/N Ratio	≥56DB(AGC OFF)
Lens	Motorized AF 6-50mm IR Lens
Viewing Angle	Horizontal: 53-9 Degree
White Balance	AUTO/AUTO EXT/PRESET/MANUAL
BackLight Compensation	OFF/BLC
HLC	OFF/HLC
Day&Night	AUTO/COLOR/B&W/EXTERN
OSD	Support (Built-in)
AUTO Gain Control	ON (Default), 0-20 steps
SENSE-UP	OFF/x2/x4/x8/x16/x32
3DNR	AUTO
True WDR	Default OFF (≥120DB)
Auto Exposure Mode	AUTO/MANUAL/FLICKER
Mirror	OFF/Low/Middle/High
Flip	OFF/ON
Motion	0-10 steps
Privacy Mask	16 masks
Defog	OFF/ON, Low/Middle/High
General	
Power Supply	Dual Voltage
Current Consumption	DC12V:1400mA(MAX)/AC24V:400mA(MAX)
IP Rating	IP67
Dimension	11.0"×4.4×3.2" (280×111×81mm)
Weight	2.4lbs (1100g)
Storage Temperature	-22 °F ~ 149 °F (-30°C ~ 65°C)
Operating Temperature	-22 °F ~ 122 °F (-30°C ~ 50°C)

Ordering Information

PAR-ALLBIRA650DN: 5 Megapixel Long Range Bullet, Motorized AF 6-50mm Lens