



## PAR-ALLDRXIR28BD

5-2 Megapixel Field Selectable TVI/AHD/CVI/CVBS, Outdoor Vandal Dome, 65.6' IR Range, True WDR, 12VDC&24V AC Power Input

### Features

- 5-2 Megapixel Field Selectable\*\*, Sony Sensor and Fuhan 4K DSP
- All-in-One Technology (TVI/AHD/CVI/Analog 960h)
- Fixed 2.8mm IR Lens
- True Day/Night
- True WDR
- 65.6' Smart IR Range
- Built-in OSD Board, Built-in Dip Switch
- Internal Built-in Balun and BNC, without Camera Leads
- Up The Cable (UTC) Function
- IP67 Weatherproof
- IK10 Vandal Resistant
- Built-in 12VDC&AC24V Operation
- Built-in 12VDC Output, 100mA Max
- Through InVid Tech DVR: Free App, CMS & MAC Client
- NDAA Compliant

Camera	PAR-ALLDRXIR28BD
Filter	Removable IR Cut Filter
Image Sensor	1/2.8" 5Mega-pixel Sony CMOS
Pixels	2592(H)*1944(V)
Video Output	TVI:5MP 20/12.5 FPS, 4MP/2MP 30/25 FPS AHD:5MP 20/12.5 FPS, 4 MP / 2MP 30/25 FPS CVI:4MP 30/25 FPS, 2 MP 30/25 FPS CVBS
Video Output By Default	TVI: 5MP @ 20 FPS AHD:2MP @ 30 FPS CVI: 2MP @ 30 FPS CVBS
Min Illumination	0Lux(3PCs led ON)
Vertical Frequency	NTSC:60Hz PAL:50Hz
IR Range	65.6 Feet
S/N Ratio	≥54DB
Lens	Fixed 2.8mm IR Lens
Viewing Angle	Horizontal: between 99-107 Degree
White Balance	ATW (PRO default), Gray World Optional
BackLight Compensation	OFF (Default)
Day&Night	Default EXT (B/W, Color, AUTO Optional)
OSD	Support
AUTO Gain Control	ON (Default)
3DNR	AUTO
True WDR	Default OFF ( ≥120DB)
Auto Exposure Mode	Default GLOBAL
Defog	OFF/ON
<b>General</b>	
Power Supply	DC12V ±10%&AC24V±10%
Current Consumption	DC12V:550mA(Max)/AC24V:210mA(Max)
IP Rating	IP67
Dimension	4.49"x 3.22" (114 x 81.8 mm)
Weight	1.1lbs (500g)
Storage Temperature	-22 °F +149 °F (-30°C ~ 65°C)
Operating Temperature	-22 °F+122 °F (-30°C ~ 50°C)

### Ordering Information

**PAR-ALLDRXIR28BD:** 5-2 Megapixel Field Selectable, 2.8mm