



PAR-VARIBULLET2 2 Megapixel 2.8-12mm Bullet,
Field Selectable TVI/AHD/CVI/Analog Output, True Day/
Night, DWDR, 164' IR Range, UTC, IP66, 12VDC

Features

- 2 Megapixel (1920 x 1080) Resolution
- Varifocal 2.8-12mm Lens
- Field Selectable: TVI/AHD/CVI/Analog Output (must use compatible DVR to change back once switched from TVI output)
- True Day/Night
- Digital WDR
- 164' IR Range
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- 12VDC Only Operation

Camera	PAR-VARIBULLET2
Image Sensor	1/2.9" CMOS
Resolution	1920 x 1080
Image System	PAL / NTSC
Auto Iris	Fixed Iris
Min Illumination	0 Lux (IR ON)
Lens	2.8-12 mm
Field of View	Horizontal: 91.7°-33.1° Vertical: 60.2°-19°
Lens Mount	D14
IR Distance	164 ft
Water-proof & Vandal Proof	IP66
Vide Output	TVI (Field Selectable: Must use compatible DVR to change once switched from TVI)
Image Size	1080P (1920 x 1080)
Frame Rate	30fps (60Hz), 25fps (50Hz)
Angle Adjustment	Any angle
Functions	
Screen Display	2 languages supported, Chinese/English
Function Control	OSD
Day & Night	Yes (ICR)
BLC & HLC	Yes
WDR	Digital WDR
Digital NR	Yes
Defect Correction	Live defective pixel correction
S/N Ratio	> 52dB (AGC off)
Electronic Shutter	1/50s ~ 1/100000s (PAL); 1/60 ~ 1/00000s (NTSC)
AGC	Yes
White Balance	ATW, AWC→SET, Manual
Advanced Image	Sharpness, saturation, brightness, etc. are adjustable
Other	
Power Supply	DC12V (±10%)
Working Environment	-4° ~ 122°F (-20°C ~ 50°C) 10% ~ 90% humidity
Dimensions	Φ4.29" x 11.18" (Φ109 X 284mm)

Ordering Information

PAR-VARIBULLET2: 2 Megapixel Bullet, 2.8-12mm