Eaton E90-24MCC-FW



Eaton Wheelock E70/E90 speaker strobe, xenon, ceiling, white, FIRE, clear lens, 15/30/75/95 cd, 25/70V, indoor



General specifications

Product NameCatalog NumberEaton Wheelock E70/E90 speaker strobeE90-24MCC-FWUPCProduct Length/Depth7866971316602.7 inProduct HeightProduct Width7.26 in7.26 in

Product Weight

1.894 lb

Compliances

Not Applicable



defaultTaxonomyAttributeLabel

Compliance and standards	Brochures
UL	Wheelock EH high fidelity speaker brochure
FCC	wheeloek Erringh heelty speaker bioentile
CSFM	Catalogs
	Wheelock life safety notification appliances catalog CA450002EN,
Mounting Method	Canada
Ceiling	Wheelock life safety notification appliances catalog CA450001EN
Housing color	Wheelock life safety notification appliances catalog CA450003FR, French
White	Canadian
Housing material	Drawings
UV stabilized plastic	wheelock-e70-speaker-strobe-drawing
Lens color	Wheelock EMNA dual strobe drawing
Clear	wheelock-e90-speaker-strobe-drawing
Lens material	Installation instructions
Lexan	wheelock-e70h-e90h-speaker-strobe-install-sheet-P85327
Lovan	wheelock-e70-e90-speaker-strobe-install-sheet-P84398
Lamp type	wheelock-e70-speaker-strobe-install-sheet-P83934
Xenon	
Current draw (DC)	wheelock-et70mcw-et90mcw-speaker-strobe-install-sheet-P83933
0.065/ 0.105/ 0.189 /0.249	wheelock-et70mcch-et90mcch-speaker-strobe-install-sheet-P84454
	wheelock-et70mcc-et90mcc-speaker-strobe-install-sheet-P84396
Frequency range - max	wheelock-et70mcwh-et90mcwh-speaker-strobe-install-sheet-P84453
4000 Hz	Selling policy and T&Cs
Frequency range - min	Wheelock E50, E60, E70, E90 UL Listings
400 Hz	
Tone (Coloctable)	Wheelock EH speaker strobe CSFM listing
Taps (Selectable)	Wheelock E speaker strobe CSFM listing
1/8 watt -2 watts: 1/8, 1/4 , 1/2 , 1 , 2	Specifications and datasheets
L ottoring	

Resources

Lettering

FIRE

Operating Temperature 33.8°F to 120.2°F (0°C to 49°C) & maximum humidity of 93%

Indoor/outdoor

Indoor

Candela settings

15 cd 30 cd 75 cd 95 cd

Wheelock Emergency Mass Notification data sheet

Eaton Specification Sheet - E90-24MCC-FW

wheelock-mounting-accessories-data-sheet

whee lock-et 70-et 90-speakers-strobes-data-sheet-TD450031 EN

wheelock-weatherproof-appliances-data-sheet-TD450112EN

wheelock-e70e90-speakers-strobes-data-sheet-TD450024EN

wheelock-e70h-e90h-speakers-strobes-data-sheet-TD450018EN

Technical data sheets

Voltage

25 V 70 V

Sound level (dBA)

Up to 87 dB at 10 ft: 74,77,80,82,85



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Right Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia