# **Eaton ELSPSTRC**

# Catalog Number: ELSPSTRC

Eaton Eluxa high fidelity speaker strobe, LED, ceiling, red, FIRE, clear lens, 15/30/75/110/150/177 cd, 25/70V, indoor

# General specifications



Product Name Catalog Number
Eaton Eluxa high fidelity speaker strobe ELSPSTRC

UPC Product Height

786697009655 3.64 in

Product Diameter Product Weight

6.2 in 1.86 lb

Compliances Certifications

Not Applicable Contact Manufacturer



# **Product specifications**

## Mounting Method

Ceiling

Housing color

Red

Indoor/outdoor

Indoor

Housing material

Plastic

Lettering

**FIRE** 

Voltage

24 V

25 V

70 V

## **Operating Temperature**

32°F to 122°F (0°C to 50°C)

## Compliance and standards

UL

ULC

FCC

# Strobe specifications

Lamp type

LED

Candela settings

15 cd

30 cd

75 cd

95 cd

150 cd

177 cd

### Current draw (DC)

0.022

0.030

0.060

0.086

0.125

0.185

Lens color

Clear

Lens material

Lexan

# Speaker specifications

Frequency range - min

300 Hz

Frequency range - max

8000 Hz

Sound level (dBA)

75/79/82/85/87

Taps (Selectable)

1/8, 1/4, 1/2, 1, 2

## Resources

#### **Brochures**

Eluxa family brochure

Eluxa product cross reference

### Catalogs

Wheelock life safety notification appliances catalog CA450001EN

### **Drawings**

Eluxa speaker strobe wall drawing

Eluxa speaker strobe ceiling drawing

#### Installation instructions

Eluxa speaker wall install sheet P85757

Eluxa speaker ceiling install sheet P85758

## Selling policy and T&Cs

Eluxa UL listing

## Specifications and datasheets

Eaton Specification Sheet - ELSPSTRC

#### Technical data sheets

Eluxa high fidelity speaker data sheet

Eluxa high fidelity amber lens speaker strobes data sheet

wheelock-mounting-accessories-data-sheet



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia