Eaton ELSPSTW

Catalog Number: ELSPSTW

Eaton Eluxa high fidelity speaker strobe, LED, wall, white, FIRE, clear lens, 15/30/75/110/135/185 cd, 25/70V, indoor



General specifications

Contact Manufacturer

Product Name	Catalog Number
Eaton Eluxa high fidelity speaker strobe	ELSPSTW
UPC	Product Length/Depth
786697009662	4.56 in
Product Height	Product Width
6.35 in	2.95 in
Product Weight	Compliances
1.75 lb	Not Applicable
Certifications	



Product specifications

Mounting Method Wall	Lamp type LED
Housing color	Candela settings
White	15 cd
Indoor/outdoor	30 cd
	75 cd
Indoor	110 cd
Housing material	135 cd
Plastic	185 cd
Lettering	Current draw (DC)
FIRE	0.022
Voltage	0.030
24 V	0.060
25 V	0.086
70 V	0.125
10 1	0.185
Operating Temperature	
32°F to 122°F (0°C to 50°C)	Lens color
	Clear
Compliance and standards	La construction de la
UL	Lens material
ULC	Lexan
FCC	

Speaker specifications

Strobe specifications

Frequency range - min 300 Hz

Frequency range - max 8000 Hz

Sound level (dBA)

75/79/82/85/87

Taps (Selectable)

1/8, 1/4, 1/2, 1, 2

Resources

Brochures Eluxa family brochure Eluxa product cross reference

Catalogs

Wheelock life safety notification appliances catalog CA450001EN

Drawings

Eluxa speaker strobe wall drawing

Eluxa speaker strobe ceiling drawing

Installation instructions

Eluxa speaker wall install sheet P85757

Eluxa speaker ceiling install sheet P85758

Selling policy and T&Cs

Eluxa UL listing

Specifications and datasheets

Eaton Specification Sheet - ELSPSTW

Technical data sheets

Eluxa high fidelity amber lens speaker strobes data sheet

Eluxa high fidelity speaker data sheet

wheelock-mounting-accessories-data-sheet



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Right Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia