# Eaton ELSPSTWC

## Catalog Number: ELSPSTWC

Eaton Eluxa high fidelity speaker strobe, LED, ceiling, white, FIRE, clear lens, 15/30/75/110/150/177 cd, 25/70V, indoor



Product Name	Catalog Number
Eaton Eluxa high fidelity speaker strobe	ELSPSTWC
UPC	Product Height
786697009679	3.64 in
Product Diameter	Product Weight
6.2 in	1.86 lb
Compliances	Certifications
Not Applicable	Contact Manufacturer





## Product specifications

Mounting Method	Lamp type
Ceiling	LED
Housing color	Candela settings
White	15 cd
Indoor/outdoor	30 cd
Indoor	75 cd
	95 cd
Housing material	150 cd
Plastic	177 cd
Lettering	Current draw (DC)
FIRE	0.022
Voltage	0.030
24 V	0.060
25 V	0.086
70 V	0.125
	0.185
Operating Temperature	
32°F to 122°F (0°C to 50°C)	Lens color
	Clear
Compliance and standards	Lens material
UL	
ULC	Lexan
FCC	

## Strobe specifications

## Speaker specifications

Frequency range - min 300 Hz

Frequency range - max 8000 Hz

Sound level (dBA)

75/79/82/85/87

Taps (Selectable)

1/8, 1/4, 1/2, 1, 2

#### Resources

Brochures Eluxa family brochure Eluxa product cross reference

#### Catalogs

Wheelock life safety notification appliances catalog CA450001EN

#### Drawings

Eluxa speaker strobe ceiling drawing

Eluxa speaker strobe wall drawing

#### Installation instructions

Eluxa speaker wall install sheet P85757

Eluxa speaker ceiling install sheet P85758

#### Selling policy and T&Cs

Eluxa UL listing

#### Specifications and datasheets

Eaton Specification Sheet - ELSPSTWC

#### Technical data sheets

wheelock-mounting-accessories-data-sheet

Eluxa high fidelity amber lens speaker strobes data sheet

Eluxa high fidelity speaker data sheet



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Right Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia