

# Eaton RSSWP-2475W-FR

Catalog Number: RSSWP-2475W-FR

Eaton Wheelock RSS strobe, xenon, red, FIRE, clear lens, 30 cd indoor , 115/180 cd outdoor, 24V

## General specifications



Product Name	Catalog Number
Eaton Wheelock RSS strobe	RSSWP-2475W-FR
UPC	Product Length/Depth
786697290138	4.409 in
Product Height	Product Width
0.59 in	4.409 in
Product Weight	Compliances
0.394 lb	Not Applicable

## defaultTaxonomyAttributeLabel

### Compliance and standards

CSFM

FM

UL

MEA

ULC

### Nominal voltage

24 V

### Voltage type

DC

### Lens color

Clear

### Material housing

Plastic

### Color housing

Other

### Mounting Method

Surface mounting

### Standby-time up to

0 hour

### Ambient temperature - max

66 °C

### Ambient temperature - min

-40 °C

### Lamp type

Incandescent lamp

### Humidity (Non Condensing) - Max

95 %

### Humidity (Non Condensing) - Min

0 %

### Operating temperature - max

66 °C

### Operating temperature - min

-40 °C

### System typology

Conventional (Non-addressable)

## Resources

### Catalogs

Wheelock life safety notification appliances catalog CA450001EN

### Drawings

Wheelock EMNA dual strobe drawing

Wheelock RSS strobe drawing

### Installation instructions

wheelock-rss-mcch-strobe-ceiling-install-sheet-P84442

wheelock-rss-strobe-wall-install-sheets-P83911

wheelock-rss-1575-strobe-install-sheet-P84233

wheelock-rss-strobe-ceiling-install-sheets-P84394

wheelock-rss-strobe-colored-lens-install-sheet-P84517

wheelock-rss-mcwh-strobe-wall-install-sheet-P84450

wheelock-rss-strobe-red-lens-install-sheet-P83884

### Selling policy and T&Cs

Wheelock RSS CSFM listing 0785-0141

Wheelock audible visual appliances UL listing

### Specifications and datasheets

Eaton Specification Sheet - RSSWP-2475W-FR

### Technical data sheets

wheelock-colored-lens-data-sheet-TD450087EN

wheelock-rss-strobes-data-sheet-TD450040EN

wheelock-mounting-accessories-data-sheet

wheelock-weatherproof-appliances-data-sheet-TD450112EN

Wheelock Emergency Mass Notification data sheet

## Product branding

Wheelock

## Integrated function

Flashlight

## UL certification standards

UL 1638 (Visual Signaling Devices)

UL 1971 (Signalling for Hearing Impaired)

## Cable entry

Rear

## Mounting position

Wall surface (internal)

## Light color

White

## System wiring

2.05 mm - 1.02 mm



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)