



**ULT-P4DRIR** 4 Megapixel IP Plug & Play Mini Rugged Dome, WDR, 100' IR Range, PoE/DC12V, SD Card Slot

4 Megapixel  
Plug & Play

Fixed Lens

H.264 / H.264+

True  
Day/Night

True WDR

IR  
100' Range

IP66  
Weather Resistant

IK10  
Vandal Resistant

PoE/DC12V

ONVIF

SD Card Slot

Free App  
iOS & Android

FREE CMS

Free MAC Client

Features

- 4 Megapixel (2688 x 1536) Resolution
- Fixed Lens
- H.264/H.264+, MJPEG Compression
- True Day/Night
- True WDR 120dB
- 100' IR Range
- IP66 Weather Resistant
- IK10 Vandal Resistant
- 12VDC/PoE Operation
- ONVIF
- SD Slot for Local Storage: Up to 128GB
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free Mac Client

Ordering Information

**ULT-P4DRIR28:** 4 Megapixel Dome, 2.8mm, White

**ULT-P4DRIR4:** 4 Megapixel Dome, 4mm, White

**ULT-P4DRIR6:** 4 Megapixel Dome, 6mm, White

**ULT-P4DRIR28B:** 4 Megapixel Dome, 2.8mm, Black

Model Number	ULT-P4DRIR
Image Sensor	1/2.8" progressive scan CMOS
Min. illumination	0.01 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter time	1/30s ~ 1/100,000s
Lens	4mm @ F2.0, angle of view: 75.8° (2.8mm, 6mm, 12mm optional)
Angle adjustment	Pan: -90° ~ 90°, tilt 0° ~ 75°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR 120db
Day & night	IR cut filter with auto switch
Video compression	H.264 / MJPEG / H.264+
Dual stream	Yes
Max. image resolution	4 MP CMOS, 2688x1520
Frame rate	20fps (2688x1520), 30fps (1920x1080)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
Network Storage	NAS
BLC	Yes, zone configurable
On Board Storage	Micro SD slot, up to 128GB
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Interoperability	ONVIF, PSIA, CGI
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	14°F ~ 104°F (-10°C ~ 40°C) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max, 5W
Ratings	IP66 / IK10
IR range	Up to 100ft
Dimensions	Ø 4.4" x 3.2" (111.7 x 81.28mm)
Weight	1.1 lbs (500g)

Mounting Options



IUM-DRJB1:  
Small Dome  
Junction Box #1



IUM-BRCM1\*  
Corner Mount #1



IUM-DRWM1:  
Small Dome  
Wall Mount #1



IUM-BRPM1\*  
Pole Mount #1

**4 MEGAPIXEL PLUG & PLAY**

*\*To use these mounts with the selected cameras drill the holes needed into the mount using the diagram included with the camera. InVid Tech. reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.*