



VIS-LRPOE4-2

4-Port PoE Switch with 2 Uplink Ports

Features

- Multiple working modes to address your business needs: Normal, Secure and Surveillance
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 820 ft transmission distance on surveillance mode
- Support buffer optimization
- All metal housing, safe and reliable

Model	VIS-LRPOE4-2
Standards	IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at
Switching capacity	1.2Gbps
Forwarding performance	0.90Mpps
Packet Buffer	768Kbit
MAC	2K
Dimensions (WxDxH)	6.3" x 3.7" x 1.3" (160 x 93 x 32mm)
Weight	< 1.3 lb (0.6kg)
Power supply	AC: 100-240V, 50/60Hz
PoE	802.3af/af
Max. PoE Power	Max capacity: 65W
	Max capacity for single port: 30W
Switch Power	67W
Surge Protection	Common mode $\pm 6KV$ Differential mode $\pm 4KV$
Electrostatic standard	Common mode $\pm 6KV$ Differential mode $\pm 8KV$
Cooling Fans	0
Mean Time Between Failure(MTBF)	>50000 hours
Operating temperature	32°F-104°F (0°C-40°C)
Operating humidity	10%~90% (noncondensing)
Storage humidity	5%~90% (noncondensing)
Indicator	PWR: Steady on: AC input is normal Off: No AC input
	PoE: Off: No PoE power supply Steady on: PoE power supply is normal Flashing: PoE power supply is abnormal
	LINK/ACT: Off: No link Steady: Linked at 10/100Mbps Flashing: Transmitting data
Working Mode	Default(Normal mode) : All ports can communicate with each other. EXTEND(Surveillance mode): Transmission distance up to 820 ft (250m) ,also downlink ports can communicate only with uplink ports.

Ordering Information

VIS-LRPOE4-2: 4-Port PoE Switch with 2 Uplink Ports

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.