



VIS-LRPOE8-2A

8-Port PoE Switch with 2 Uplink Ports

Features

- 8x10/100Mbps Ethernet Ports
- 2 Uplink Ports, All 100 Mbps
- All 100Mbps ports support PoE
- Up to 820 ft transmission distance on surveillance mode
- PoE complies with IEEE802.3af/at, up to 30W for single port
- Easy-to-use, no need to configure
- High quality with all metal housing

Model	VIS-LRPOE8-2A (VIS-LRPOE8-1*)
Ports	10x 100Mbps network ports (RJ45), including 8 PoE ports
Standards	IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at
Switching capacity	2Gbps
Forwarding performance	1.49Mpps
Packet Buffer	2Mbit
MAC	8K
Dimensions (WxDxH)	8.7" x 5.9" x 1.7" (220 x 150 x 44 mm)
Weight	2.7lb (< 1.22kg)
Power supply	AC: 100-240V, 50/60Hz
PoE	802.3at/af
Max. PoE Power	Max capacity: 120W, Max capacity for single port: 30W
Cooling Fans	0
Mean Time Between Failure (MTBF)	>50000 hours
Operating temperature	32°F-104°F (0°C-40°C)
Operating humidity	10%~90% (non-condensing)
Storage humidity	5%~90% (non-condensing)
Indicator	<p>PWR: Steady on: AC input is normal Off: No AC input</p> <p>PoE: Off: No PoE power supply, Steady on: PoE power supply is normal Flashing: PoE power supply is abnormal</p> <p>LINK/ACT: Off: No link, Steady: Linked at 10/100Mbps Flashing: Transmitting data</p>
Working Mode	Default(Normal mode): All ports can communicate with each other.

Ordering Information

VIS-LRPOE8-2A (VIS-LRPOE8-1*): 8-Port PoE Switch with 2 Uplink Ports

*Actual Part number is VIS-LRPOE8-1. VIS-LRPOE8-2A shown for internal inventory separation.

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.