



VIS-POE8-2

8 Port PoE Switch with 2 Up-link Ports

Features

- Conforms to IEEE802.3u, IEEE802.3z, IEEE802.3af, IEEE802.3at
- Provides 10/100Base-TX ports, 2 10/100/1000 Base-TX
- Provides PoE Injector and 125W Power Adaptor
- High Back-Plane Bandwidth 5.6G bps
- IEEE802.3x Flow Control

Product	VIS-POE8-2
Power	
Power Supply	External Power Adaptor
Voltage Range	DC52V~55V
Consumption	< 6W
Ethernet	
Speed	1-8 PORT: 10/100 Mbps If Extension mode is on, distance up to 800', but all ports 10m only Uplink: 10/100/1000 Mbps
Transmission Distance	328 Ft. (100 meters)
Network Switch	
Ethernet Standard	IEEE802.3 / IEEE802.3u / IEEE802.3af / IEEE802.3at
Switching Capacity	5.6G
Transfer Rate	14,880 pps for 10 Mbps 148,800 pps for 100 Mbps
MAC Address	4k Mac Address
G1.G2	
On	The port is connecting. Orange is 10/100 Mbps. Green is 1000 Mbps.
LINK/ACT	
On	Green- The port is connecting
Blinks	The port is receiving or transmitting data
Off	The port is not linked successfully with the device
POE	
On	Orange- PD is connected
Off	No PD is connected or power forwarding fails
Working Environment	
Working Temperature	32 ~ 104°F (0-40°C)
Storage Temperature	-40 ~ 158°F (-40~70°C)
Humidity Non-Condensing	0~85%
Mechanical	
Dimensions (L x W x H)	7.4 x 3.9 x 1.1 inches (190 x 100 x 28 mm)
Color	Gray

Ordering Information

VIS-POE8-2: 8-Port PoE Switch