

2MP HD-TVI IR Dome Camera with Junction Box

VLD5

2.8mm fixed lens, white housing









Features

- Supports up to 2MP @ 30fps
- Full HD resolution over coax
- Supports HD-TVI, CVI, AHD, and 960H Analog
- IR Range: 65' (depending on scene reflection)
- True WDR (wide dynamic range)
- 12VDC Operation (power supply not included)
- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant

- Junction box included
- 5 year warranty





Camera Specifications 1/2.8" CMOS, 2MP Image Sensor Minimum Illumination Color: 0.001 lux @F1.2, (AGC ON); BW: 0 lux (IR ON) Image Size 1920 x 1080 AHD/TVI/CVI/CVBS Video Output PAL/NTSC Image System Auto: 1/25s ~ 1/50000s (PAL); 1/30s ~ 1/50000s (NTSC) **Electronic Shutter** 32.8ft ~ 65.6ft IR Distance 30fps (60Hz); 25fps (50Hz) Frame Rate Lens Mount

≥ 52dB (AGC OFF)

Functions

S/N Ratio

Function Control	OSD (COC Control)
Day & Night	Yes, Smart IR
WDR	Yes
DNR	3D DNR
AGC	Yes
Auto White Balance	Yes
Compensation	BLC
Sharpness	Yes
Mirror	Yes
Image Setting	Yes
Defect Correction	Auto
Angle Adjustment	Pan (0° ~ 355°); Tilt (0° ~ 67°); Rotation (0° ~ 355°)

Operating & Unit Specifications

Power	12VDC (power supply not included)
Power Consumption	IR OFF: < 1.5W; IR ON: < 4.5W
Operating Temperature	-22°F ~ 122°F
Operating Humidity	10% ~ 90% RH
Unit Dimensions	4.69" (Dia.) x 3.46" (H)
Unit Weight	1.28 lbs.



liance with NDAA Section 889 Part B Guidelines

Optional Accessories



PSW5 12VDC **Power Supply**



TVIUTPPT HD Video Transceiver with Pigtail (Balun)



TVIUTP HD Video Transceiver



PMT1 Pole Mount (use with wall mount)



O5VIWMI Wall Mount



CIT21 Ceiling Mount



Corner Mount



FMT1 Wall Mount



CLTX1 Ceiling Mount 4" Extension



CLTX2 Ceiling Mount 8" Extension

